

Material Declaration

<Date of declaration>

Date	
------	--

<MD ID number>

MD-ID-No.	
-----------	--

<Supplier (respondent) information>

Company name	
Division name	
Address	
Contact person	
Telephone number	
Fax number	
E-mail address	
SDoC ID-No.	

<Other information>

Remark 1	
Remark 2	
Remark 3	

<Product information>

Product name	Product number	Delivered unit		Product information
		Amount	Unit	

<Material information>

This materials information shows the amount of hazardous materials contained in

Unit
1

Table	Material name	Threshold level	Present above threshold level	If yes, material mass		If yes, information on where it is used
			Yes/No	Mass	Unit	
Table A** (materials listed in appendix 1 of the Convention)	Ozon depleting substance	0.1%*				
		50 mg/kg				
		no threshold level				
		2,500 mg total tin/kg				
Table B** (materials listed in appendix 2 of the Convention)		100 mg/kg				
		1,000 mg/kg				
		1,000 mg/kg				
		1,000 mg/kg				
		50 mg/kg				
		1,000 mg/kg				
		50 mg/kg				
		no threshold level				
		1%				
Annex II*** (Additional materials)		10 mg/kg****				
		100 mg/kg				

*Please refer to footnote 18 on the "Form of Material Declaration" in the IMO Guidelines Resolution MEPC.269(68).

**Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships, 2009 (SR/CONF/45).

***Regulation EU No. 1257/2013 of the European Parliament and of the Council of 20 November 2013 on Ship Recycling and amending Regulation EC No. 1013/2006 and Directive 2009/16/EC

EMSA's Best Practice Guidance on the Inventory of Hazardous Materials, dated 2016-10-28

****Concentrations of PFOS above 10 mg/kg (0.001% by weight) when it occurs in substances or in preparations or concentrations of PFOS in semi-finished products or articles, or parts thereof equal to or above than 0.1% by weight calculated with reference to the mass of structurally or micro-structurally distinct parts that contain PFOS or for textiles or other coated materials, if the amount of PFOS is equal to or above than 1 µg/m² of the coated material.