## **Supplier's Declaration of Conformity for Material Declaration Management**

1)	SDoC No.:	TR-212-27816		
2)	Issuer's Name :	DELTA CO		
	Issuer's address :	2-1-20, TOKYO , 106004	16	
3)	Object(s) of declaration: 1)	HC SENSOR		
4)	The object(s) of the declaration de	scribed above is/are in con	nformity with the following documents	
5)	Applicable Regulations or other Document No. Title	stipulated requirements	s and documents Edition	Date of Issue
ME	EPC. 269(68) Guidlines for	the development for the Ir	nventory of Hazardous Materials	15-05-2015
E	U SRR Regulation (EU) No 1257/2	013		20-11-2013
EN	MSA Best Practice Guide on the IHN	1 2016		28-10-2016
Нс	ong Kong Int.Convention for the safe	e and environmentally sour	nd recycling of Ships , 2009 Regulation	5 Para 3.
6)	Additional Information:	ON ASBEST	OS	
	Signed for and on behalf of		69	FRIMA
Т	OKYO			NYVO
Pla	ace of Issue			No.
1	5-12-2022			
Da	te of Issue		(~ \ / D	1 +
7)	Hashimoto		L. Hashi	mola
N	ame, function		Signature	

Date: 15-12-2022

MD-ID No: DL2216700

Remark 1 A-22087629 Remark 2 825-22-0197 Remark 3 EPIC BARNES

Company Name	DELTA CO LTD
Division Name	FORWARDING LOGISTICS DEPT
Address	2-1-20, TOKYO, 1060046
Contact Person	HASIMOTO
Telephone Number	03-5449-1421
Fax Number	03-5449-3871
E-Mail Address	
SDoC ID-No	TR-212-27816

Product Name	Product Number	Delivered Unit		Product Information
		Amount	Unit	
HC SENSOR	SS231-NB-100L	6	PCS	HC SENSOR

This material information shows the amount of hazarduos materials contained in 1

Table	Ma	terial Name	Threshold level	Present above thershold level	lf ye materia		If yes,information on where it is used
				Yes/No	Mass	Unit	
	Asbestos		0.1%*	No		▼	
	Polychlorinated biphenyls (PCBs)		50 mg/kg	No		▼	
	Ozon depleting Substance	Chlorofluorocarbons (CFCs		No		▼	
		Halons		No		▼	
		Otherfully halogenated CFCs		No		▼	
		Caroon tetrachroride		No		✓	
Table A**		1,1,1-Trichlroethane	no thershold level	No		<b>_</b>	
materials listed in appendix 1 of the		Hydrochlorofluorocarbans		No		▼	
Convention		Hydrobromofluorocarbans		No		▼	
		Methyl bromide		No		▼	
		Bromochloromethane		No		▼	
	Anti-fouling system containg organotin compounds as a biocide		2500 mg total tin/kg	No		<b></b>	
	Cadmium and cadmium compounds		100 mg/kg	No		_	GENTINE?
	Hexavalent chromium and hexavalent chromium compunds		1,000 mg/kg	No		<b>_</b>	
Table B**	Lead and Lead compounds		1,000 mg/kg	No		<b>_</b>	
	Mercury and mercury componds		1,000 mg/kg	No		<b>V</b>	
materials listed in	Polyprominated biphenyl (PBBs)		50 mg/kg	No			- 11/1/(1/11/01-
appendix 2 of the Convention	Polyprominated dephenyl ethers (PBDEs)		1,000 mg/kg	No		▼	_ N -1
Convention	Polychloronaphthalenes (CI >= 3)		50 mg/kg	No		<b> </b> ▼	Olivino
			no thershold level	No		▼	
	Certain shortchain chlorinated paraffins		1%	No			
Annex II***	Perfluoroocatne sulfonic acid (PFOS)		100 mg/kg****	No		_	
(Additional materials)	Brominated Flame Retardant(HBCDD)		100 mg/kg	No		▼	

<sup>\*</sup> Please refer to footnote 18 on the "Form of Material Declaration in the IMO Guidlines Resolution MEPC 269(68)

Important Notice: The content and Specification of this form may not be changed or amended. Any Changes or Amendments by others than the author of this form constitute a breach on copyright law

<sup>\*\*</sup> Hongkong International convention for the safe and Environmentally Sound Recycing of Ships 2009 (SR CONF 45)

<sup>\*\*\*</sup> Regulation EU No 1257/2013 of the Europian Parliment and the Council of 20 November 2013 on ship Recycling and amending Regulation EC No 1013/2006 and Directive 2009/16/EC EMSA's Best Practice Guidance on the Inventory of Hazardous Materials dated 2016-10-28

<sup>\*\*\*\*</sup> Concentrations of PFOS above 10 mg/kg (0.00% by Weight) when it occurs in substances or in preparations or in concentrations of PFOS in semi-finished products or orticles or parts thereof equal to orabove than 0.1% by weight calculated with reference to the mass of structurally distinct parts that contain PFOS or for textiles or other coated materials, if the amount of PFOS is equal to or above than 1ug/m2 of the coated material