Supplier's Declaration of Conformity for Material Declaration Management

1)	SDoC No.:		TR-212-27688		
2)	Issuer's Name :		DELTA CO		
	Issuer's address :		2-1-20, TOKYO , 1060046		
3)	Object(s) of declaration :	1)	KNOB OF DIMMER		
		2)	RHEOSTAT 3KO 25W		
4)	The object(s) of the declara	tion de	scribed above is/are in conformit	with the following documents	
5)			stipulated requirements and o		D () (1
	Document No. Ti	-	41	Edition	Date of Issue
_			the development for the Invento	ry of Hazardous Materials	15-05-2015 20-11-2013
_E	U SRR Regulation (EU) No	1257/2	013 ————————————————————————————————————		
ΕN	MSA Best Practice Guide on	the IHN	1 2016		28-10-2016
Н	ong Kong Int.Convention for	the saf	e and environmentally sound recy	cling of Ships , 2009 Regulation	n 5 Para 3.
	Signed for and on behalf	of		6	SALUE SALUES
Т	Signed for and on behalf	of		6	TOWYOO:
_	_	of		6	ONVO:
Pla	ГОКҮО	of		6	TONNO:
Pla O	TOKYO ace of Issue	of			TONNO:
Pla O	TOKYO ace of Issue 19-12-2022	of		L- Hash	moto

Date: 09-12-2022

MD-ID No : DL2216356

 Remark 1
 00036056

 Remark 2
 834-22-0205

 Remark 3
 EPIC BURANO

Company Name	DELTA CO LTD
Division Name	FORWARDING LOGISTICS DEPT
Address	2-1-20, TOKYO, 1060046
Contact Person	HASIMOTO
Telephone Number	03-5449-1421
Fax Number	03-5449-3871
E-Mail Address	
SDoC ID-No	TR-212-27688

Product Name	Product Number	Delivered Unit		Product Information
		Amount	Unit	
RHEOSTAT 3KO 25W		1	PCS	RHEOSTAT 3KO 25W
KNOB OF DIMMER		2	PCS	KNOB OF DIMMER

Unit Piece ▼

This material information shows the amount of hazarduos materials contained in 1 Piece

Table	Material Name		Threshold level	Present above thershold level	lf yes, material mass		If yes,information on where it is used
				Yes/No	Mass	Unit	
	Asbestos		0.1%*	No		V	
	Polychlorinated biphenyls (PCBs)		50 mg/kg	No		▼	
		Chlorofluorocarbons (CFCs		No		▼	
		Halons		No		V	
		Otherfully halogenated CFCs		No		V	
		Caroon tetrachroride		No		▼	
Table A**	Ozon depleting Substance	1,1,1-Trichlroethane		No		▼	
materials listed in appendix 1 of the		Hydrochlorofluorocarbans		No		▼	
Convention		Hydrobromofluorocarbans	no thershold level	No		▼	
		Methyl bromide		No		▼	
		Bromochloromethane		No		\	
	Anti-fouling system containg organotin compounds as a biocide		2500 mg total tin/kg	No		▼	
	Cadmium and cadmium compounds		100 mg/kg	No		▼	arrespond
	Hexavalent chromium and hexavalent chromium compunds		1,000 mg/kg	No		V	1 t
Table B**	Lead and Lead compounds		1,000 mg/kg	No		▼	100
rabio B	Mercury and mercury componds		1,000 mg/kg	No		▼1	LOMAININ:
materials listed in	Polyprominated biphenyl (PBBs)		50 mg/kg	No		▼]	THE WILL
appendix 2 of the Convention	Polyprominated dephenyl ethers (PBDEs)		1,000 mg/kg	No		▼	
Convention	Polychloronaphthalenes (CI >= 3)		50 mg/kg	No		▼	10/11/11/01
-			no thershold level			V	
	Certain shortchain chlorinated paraffins		1%	No		▼	X 7
Annex II***	Perfluoroocatne sulfonic acid (PFOS)		100 mg/kg****	No		▼	
(Additional materials)	Brominated Flame Retardant(HBCDD)		100 mg/kg	No		▼	

^{*} Please refer to footnote 18 on the "Form of Material Declaration in the IMO Guidlines Resolution MEPC 269(68)

Important Notice: The content and Specification of this form may not be changed or amended. Any Changes or Amendments by others than the author of this form constitute a breach on copyright law

^{**} Hongkong International convention for the safe and Environmentally Sound Recycing of Ships 2009 (SR CONF 45)

^{***} Regulation EU No 1257/2013 of the Europian Parliment and the Council of 20 November 2013 on ship Recycling and amending Regulation EC No 1013/2006 and Directive 2009/16/EC EMSA's Best Practice Guidance on the Inventory of Hazardous Materials dated 2016-10-28

^{****} Concentrations of PFOS above 10 mg/kg (0.001% by Weight) when it occurs in substances or in preparations or in concentrations of PFOS in semi-finished products or orticles or parts thereof equal to orabove than 0.1% by weight calculated with reference to the mass of structurally distinct parts that contain PFOS or for textiles or other coated materials, if the amount of PFOS is equal to or above than 1ug/m2 of the coated material