MATERIAL DECLARATION (MD)

<19/09/2024>

| Date | 19/09/2024 |
|------|------------|
| | |

<MD identification number>

| ID-No. | M2417076 |
|--------|----------------|
| | 5402007-HAN- |
| | 103/2024E-O001 |

<Other information>

| Remark 1 | Vessel: | HANSIKA | |
|----------|---------|---------|--|
| Remark 2 | | | |
| Remark 3 | | | |

<Supplier (respondent) information>

| Company name | MIDDLE EAST FUJI L.L.C |
|------------------|---|
| Division name | MARINE SUPPLY |
| Address | Building No. 7, Street 4, Al Quoz Industrial Area 3, P.O.Box.19227, Dubai, United Arab Emirates |
| Contact person | Mr. Rooble Kuriakoose |
| Telephone number | +971 4 347-4444 |
| Fax number | +971 4 347-2771 |
| Email address | tech1.uae@mefgroup.com |
| SDoC ID number | M2417076 |

<Product information>

| Draduat nama | | Delivered unit | | Product information | | |
|---|----------------|----------------|------|-----------------------------------|--|--|
| Product name | Product number | Amount | Unit | Product information | | |
| JOINT SHEET GRAPHITE HIGH TEMP 2.0X1000X1000MM | 811028 | 2 | SHT | OFFER: 120X120X38MM 220-240VAC | | |
| GASKET SPIRAL WOUND WITH FURTHER DETAIL SPIRAL WOUND GASKET, ROUND SHAPE "R" GASKET SPIRAL WOUND ROUND SHAPE "R" PURE GRAPHITE WORKING PRESSURE: 30.0BAR OUTER DIAMETER (B): 270MM INNER DIAMETER (A): 240MM THICKNESS: 4MM | 8118 | 4 | PCS | | | |
| SPIRAL WOUND GASKET, ROUND SHAPE WITH INNER AND OUTER RING "IOR" GASKET SPIRAL WOUND ROUND SHAPE WITH INNER AND OUTER RING "IOR" PURE GRAPHITE WORKING PRESSURE: 30.0BAR RING OUTER DIAMETER (D): 330MM SPIRAL OUTER DIAMETER (B): 315MM RING INNER DIAMETER (D): 265MM SPIRAL INNER DIAMETER (A): 280MM THICKNESS: 4MM | 8118 | 4 | PCS | | | |
| CLOTH GLASS 1.3X1000MM | 811701 | 10 | MTR | | | |

<Materials information>

This materials information shows the amount of hazardous materials contained in

Unit
1 PCS/PKT/SHT

(Unit: kg, m, m^2 , m^3 , piece, etc.) of the product

| Table | Material name | | Threshold value | Present above threshold value? Yes / No | If yes, mater mass Mass | ial Unit | If yes, information on where it is used |
|--|-------------------------------------|----------------------------------|--------------------|---|-------------------------------|-------------|---|
| | Asbestos | Asbestos | 0.1% * | No | | | |
| Table A (materials listed in appendix 1 of the | Polychlorinated biphenyls (PCBs) | Polychlorinated biphenyls (PCBs) | 50 mg/kg | No | | | |
| | Ozone Depleting Substance (ODS) | Chlorofluorocarbons (CFCs) | No threshold | No | | | |
| Convention | | Halons | | No | | | |
|) | | Other fully halogenated CFCs | | No | | | |

| | Carbon tetrachloride | | No | | |
|-----------|--|--------------------------|----|--|--|
| | 1, 1, 1- Trichloroethane | | No | | |
| | Hydrochlorofluorocar bons | | No | | |
| | Hydrobromofluoroca rbons | | No | | |
| | Methyl bromide | | No | | |
| | Bromochloromethan e | | No | | |
| | Anti-fouling systems containing organotin compounds as a biocide | 2,500 mg total tin/kg | No | | |
| | Anti-fouling systems containing cybutryne as a biocide**** | 1000 mg/kg | No | | |
| EU SRR ** | Perfluorooctane sulfonic acid (PFOS) | 10 mg/kg | No | | |

| Table | Material name | Threshold value | Present above threshold value? | If yes, material mass | | If yes, information on where |
|-----------------------|---|-----------------|--------------------------------|-----------------------|------|------------------------------|
| | | | Yes / No | Mass | Unit | it is used |
| | Cadmium and cadmium compounds | 100 mg/kg | No | | | |
| T. I. I. D. | Hexavalent chromium and hexavalent chromium compounds | 1000 mg/kg | No | | | |
| Table B (materials | Lead and lead compounds | 1000 mg/kg | No | | | |
| listed in | Mercury and mercury compounds | 1000 mg/kg | No | | | |
| appendix 2 | Polybrominated biphenyl (PBBs) | 50 mg/kg | No | | | |
| of the | Polybrominated diphenyl ethers (PBDEs) | 1000 mg/kg | No | | | |
| Convention (| Polychloronaphthalenes (Cl >=3) | 50 mg/kg | No | | | |
| | Radioactive substances | No threshold | No | | | |
| | | value | | | | |
| | Certain shortchain chlorinated paraffins | 1% | No | | | |
| EU SRR ** | Brominated flame retardant (HBCDD) | 100 mg/kg | No | | | |

^{*} In accordance with regulation 4 of the IMO Hong Kong Convention, for all ships, new installation of materials which contain asbestos shall be prohibited. According to the UN recommendation "Globally Harmonized System of Classification and Labelling of Chemicals (GHS)" adopted by the United Nations Economic and Social Council's Sub-Committee of Experts on the Globally Harmonized System of Classification and Labelling of Chemicals (UNSCEGHS), the UN's Sub Committee of Experts, in 2002 (published in 2003), carcinogenic mixtures classified as Category 1A (including asbestos mixtures) under the GHS are required to be labelled as carcinogenic if the ratio is more than 0.1%. However, if 1% is applied, this threshold value should be recorded in the Inventory and, if available, the Material Declaration and can be applied not later than five years after the entry into force of the Convention. The threshold value of 0.1% need not be retroactively applied to those Inventories and declarations.

^{**} Additional materials to be listed, in accordance with Annex I and Annex II of the European Union Ship Recycling Regulation (Regulation (EU) No 1257/2013 No