MATERIAL DECLARATION

| <date declaration="" of=""></date> | | | | | | | | |
|---|-------------------|--|--|--|--|--|--|--|
| Date: | 26-10-2024 | | | | | | | |
| | | | | | | | | |
| <md id="" number=""></md> | | | | | | | | |
| MD-ID-No. | MD JMS-24-0062434 | | | | | | | |
| | | | | | | | | |
| <other (e.g="" applicable.)="" hull="" if="" information="" number="" shipyard,=""></other> | | | | | | | | |
| Remark 1 | | | | | | | | |
| Remark 2 | | | | | | | | |
| Remark 3 | | | | | | | | |
| | | | | | | | | |

| _ <supplier (respondent)="" information=""></supplier> | | | | | | |
|--|--------------------------------------|--|--|--|--|--|
| Company name | J.M.SOLUTIONS FZE | | | | | |
| Division name | SALES / LOGISTICS | | | | | |
| Address | P.O.BOX. 39539 RAS AL KHAIMAH, U.A.E | | | | | |
| Contact person | Murthei | | | | | |
| Telephone no | 91-7823914684 | | | | | |
| Fax no | | | | | | |
| E-mail adress | salesfive@jmsgroup.jp | | | | | |
| SDoC ID no | SDoC JMS-24-0062434 | | | | | |
| | | | | | | |

<Product Information>

| Product Name | Product Number | Delivered Unit | | Product Information |
|--------------|----------------|----------------|------|---------------------|
| | | Amount | Unit | |
| | | | | |

This material information shows the amount of hazardous materials contained in

Unit:

<Material Information> IF YES IF YES ent above Table Material Name Threshold level Information Material Mass threshold level Yes or No Amount Unit on where it is used Asbestos Asbestos 0,1% * No Table A* PCB's Polychlorinated Biphenyls (PCBs) 50 mg/kg No Chlorofluorcarbons (CFC's) No Materials Halons No listed in Other fully Halogenated CFC's No ppendix 1 Ozone depleting Carbon Tetrachloride No of the Substances No threshold level 1,1,1-Trichloroethane No onventior Hydrochlorofluorcarbons No Hydrobromofluorcarbons No Methyl Bromide No Bromochloromethane No Δ-4 Anti-fouling systems containing organotin compounds as a biocide 2500 mg total tin/kg No 1000 mg/kg Anti-fouling systems containing cybutryne as a biocide or 200 mg/kg No

| Table | Material Name | Threshold level | Present above | IF YES Material Mass | | IF YES |
|----------------------------|---|-----------------|-----------------|-------------------------|------|---------------------|
| Table | material Name | | threshold level | | | Information |
| | | | Yes or No | Amount | Unit | on where it is used |
| | Cadmium & Cadmium Compounds | 100 mg/kg | No | | | |
| Table B** | Hexavalent Chromium and Hexavalent Chromium Compounds | 1,000 mg/kg | No | | | |
| | Lead and Lead Compounds | 1,000 mg/kg | No | | | |
| Materials | Mercury and Mercury Compounds | 1,000 mg/kg | No | | | |
| listed in | Polybromated Biphenyl (PBB's) | 50 mg/kg | No | | | |
| appendix 2 | Polybrominated Dephenyl Ethers (PBDE's) | 1,000 mg/kg | No | | | |
| of the | Polychloronaphtalenes (CI>=3) | 50 mg/kg | No | | | |
| Convention | Radioactive substances | No thr.level | No | | | |
| | Certain Shortchain Chlorinated Paraffins | 1% | No | | | |
| | | 1 | | | | |
| Annex II*** (Additional | Perfluorooctane sulfonic acid (PFOS) | 10 mg/kg**** | No | | | |
| | Flame Retardant (HBCDD) | 100 mg/kg | No | | | |

*Please refer to footnote 18 on the "Form of Material Declaration" in the IMO Guidelines Resolution MEPC 379(80).
**Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships, 2009 (SR/CONF/45).
***Regulation EU No. 1257/2013 of the European Parliament and of the Council of 20 November 2013 on Ship Recycling and amending Regulation EC No. 1013/2006 and Directive 2009/16/EC

EMA's Best Practice Guidance on the Inventory of Hazardous Materials, dated 2016-10-28 ""Concentrations of PFOS above 10 mg/kg (0.001% by weight) when it occurs in substances or in preparations or concentrations of PFOS in semi-finished products or articles, or parts thereof equal to or above than 0.1% by weight calculated reference to the mass of structurally or micro-structurally distinct parts that contain PFOS or for textiles or other coated materials, if the amount of PFOS is equal to or above than 1 µg/m² of the coated material