

MATERIAL DECLARATION

Date:	2025-07-23
MD ID Numb	er>
MD-ID-No.	FB25077145
WID-ID-NO.	PB2507/145
	hation (e.g Shipyard, Hull Number if applicable.)>
Other Inform	nation (e.g Shipyard, Hull Number if applicable.)>

<supplier (respondent)="" information=""></supplier>						
Company name	DINTEC Co. Ltd.					
Division name	SALES					
Address	DINTEC Bl dg., Jungang-Daero 309, Dong-Gu, Busan, 601-836					
Contact person	Jinny Yoon					
Telephone no	82-51-664-1158					
Fax no	82-51-462-7907					
E-mail adress	inny.yoon@dintec.co.kr					
SDoC ID no	SDoC-FB25077145					

<product information=""></product>							
Product Name	Product Number		red Unit	Product Information			
		Amount	Unit				
SWING CHECK VALVE V1- 5K 25	V1	1	PCS				
SWING CHECK VALVE V2 - 5K 40	V2	1	PCS				
WATER EJECTOR NOZZLE	NOZZLE: SUS 304	1	PCS				
SIGHT GLASSMATERIAL : TEMPERE		1	PCS	D GLASS FOR SIGHT GLASS CONN. OD: 104MM THIK: 10 M			
GASKETMATERIAL : NEOPRENE RUB		4	PCS	BER FOR SIGHT GLASS CONN OD: 105MM ID: 76MM THIK: 1.5 M			
GASKETMATERIAL : NEOPRENE RUB		4	PCS	BER FOR CONDENSER COVER OD: 520 MM ID: 400 MM THIK: 3.0			
SIGHT GLASSMATERIAL : TEMPERE		1	PCS	D GLASS FOR FRESH WATER CONN. OD: 61MM THIK: 10 MM			
GASKETMATERIAL : NEOPRENE RUB		4	PCS	BER FOR FRESH WATER OUTLET OD: 63 MM ID: 51 MM THIK: 1.			

This material information shows the amount of hazardous materials contained in

1 piece

Material	Information>

Table	Material Name		Threshold level	Present above threshold level Yes or No	IF YES Material Mass Amount Unit		IF YES Information on where it is used
	Asbestos	Asbestos	0,1%*	No			
Table A**	PCB's	Polychlorinated Biphenyls (PCBs)	50 mg/kg	No			
		Chlorofluorcarbons (CFC's)		No			
Materials		Halons		No			
listed in		Other fully Halogenated CFC's		No			
appendix 1	Ozone depleting	Carbon Tetrachloride]	No			
of the	Substances	1,1,1-Trichloroethane	No threshold level	No			
Convention		Hydrochlorofluorcarbons		No			
		Hydrobromofluorcarbons		No			
		Methyl Bromide		No			
		Bromochloromethane		No			
	Anti-fouling systems containing organotin compounds as a biocide		2,500 mg total tin/kg	No			
	Anti-fouling systems contaning cybutryne		1,000 mg/kg	No			

Table	Material Name	Threshold level	Present above threshold level	IF YES Material Mass		IF YES Information
			Yes or No	Amount	Unit	on where it is used
	Cadmium & Cadmium Compounds	100 mg/kg	No			
Table B**	Hexavalent Chromium and Hexavalent Chromium Compounds	1,000 mg/kg	No			
	Lead and Lead Compounds	1,000 mg/kg	No			
Materials	Mercury and Mercury Compounds	1,000 mg/kg	No			
listed in	Polybromated Biphenyl (PBB's)	50 mg/kg	No			
appendix 2	Polybrominated Dephenyl Ethers (PBDE's)	1,000 mg/kg	No			
of the	Polychloronaphtalenes (CI>=3)	50 mg/kg	No			
Convention	Radioactive substances	No thr.level	No			
	Certain Shortchain Chlorinated Paraffins	1%	No			
Annex II*** (Additional	Perfluorooctane sulfonic acid (PFOS)	10 mg/kg****	No			
Materials)	Flame Retardant (HBCDD)	100 mg/kg	No			

yj, yoon

(Date, Signature and Company Stamp)

DINTEC CO., LTD.
DINTEC Building,(Choryang-dong)
309, Jungang-daero, Dong-gu,
Busan, Korea

IMPORTANT NOTICE: Any significant change in material content may render this declaration invalid.

Please refer to footnote 18 on the "Form of Material Declaration" in the IMO Guidelines Resolution MEPC.405(83).

"Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships, 2009 (SR/COMF/45).

"Regulation EU No. 1257/2013 of the European Parliament and of the Council of 20 November 2013 on Ship Recycling and amending Regulation EC No. 1013/2006 and Directive 2009/16/EC EM/SA/S Best Practice Guidance on the Inventory of Hazardous Materials, dated 2016-10-28

""Concentrations of PFOS above 10 mg/kg (0.001% by weight) when it occurs in substances or in preparations or concentrations of PFOS in semi-finished products or articles, or parts thereof equal to or above than 0.1% by weight calculated reference to the mass of structurally or micro-structurally distinct parts that contain PFOS or for textiles or other coated materials, if the amount of PFOS is equal to or above than 1 µg/m² of the coated material